

Catalog No

Project

Date

Prepared By

LINEAR STRIP ETH SERIES

Product Description

Gielight LED Linear Strip provides industry-leading performance paired with high efficacy and dimming/control capabilities. The low profile design allows for quick installation. Rated at over 150 LPW, and backed by industry leading 7 year warranty.



FEATURES

4ft

8ft

30W/ 40W

60W

4000K / 5000K

Efficacy up to 153 LPW

7 Year Warranty

0 – 10V Dimming

Rated Life 75,000 hours

Operating Temperature
-20°C to 40°C

Construction & Installation

Gielight Linear Strip features a distinct white matte finish with a well constructed diffuser with no additional frame needed. Quick installation with back housing that includes holes and slots for different mounting options. Easy to daisy chain from one fixture to another.

Electrical & Operations

Our Linear Strip series is universal voltage (120-277V) with a reliable driver equipped with 0-10V dimming capability. Can operate in temperatures -20°C to 40°C. Fixture utilizes high-efficacy LED packages to maintain overall cool fixture temperatures.

Applications

A wide variety of utility applications including parking garage, warehouses, large retail stores, offices storage units, restrooms and stairwells.

Certification

UL Listed. All components have UL certification. UL Class 2. Driver: SCP, OTP, OVP protection, FCC Part 15 Class B, UL8750 Class 2. DLC Premium.

Warranty

7 year warranty with a 75,000 hour rated L70. See warranty documentation for more detail information.




ORDERING INFORMATION

Example : ETH-M02-30W-H 4000K

Nomenclature	Series	Form	Wattage	Voltage	Color Temp.
ETH	M	02	30W	H	4000K
ETH = Etherium	M = Linear Strip Series	01 = 4 feet	30W = 30 Watts	H=120-277V	4000K = 4000K
		02 = 4 feet	40W = 40 Watts		5000K = 5000K
		03 = 8 feet	60W = 60 Watts		

Specifications and Dimensions subject to change without notice

SPECIFICATION	
PERFORMANCE SUMMARY	
Input Voltage	120-277V
Input Frequency	50/60 Hz
Wattage	See Performance table
Lumens	See Performance Table
Efficacy	>153 LPW
CRI	83+
CCT	4000K / 5000K
Rated Life	75,000 Hr
L70	>72,000 Hr
Power Factor	>0.9
THD	<15%
Dimming	0-10V
Operating Temp.	-20°C to 40°F



CARTON DIMENSIONS AND WEIGHT			
Model	Carton	Weight	PCS/BOX
4ft	49.6" x 11.81" x 11.81"	46.29 LBS	6pcs
8ft	98.42" x 4.72" x 4.72"	15 LBS	1 pcs

PERFORMANCE DETAILS							
				4000K		5000K	
Form Factor	Catalog No.	Rated Wattage	Tested Wattage	Total Lumens	Efficacy LPW	Total Lumens	Efficacy LPW
4ft	ETH-M01-40W-H	37.97W	37.97W	5747 lm	151	5844 lm	152.8
4ft	ETH-M02-30W-H	31.1W	31.1W	4695 lm	150.7	4701 lm	152.1
8ft	ETH-M03-60W-H	60.8W	60.8W	9233 lm	151.8	9245 lm	153

Specifications and Dimensions subject to change without notice